

Servo Motor Cables

SL 802 C TPE/PUR feedback cable with overall copper screen

SL 803 C TPE/PUR transmission cable with overall copper screen

suitable for
cable tracks

SAB Servo

BRÖCKSKES · D-VIERSEN · SL 802 C 9 x 0,5 mm² CE



Marking for SL 802 C 08020050:

SAB BRÖCKSKES · D-VIERSEN · SL 802 C 9 x 0,5 mm² CE



4 x 2 x 0,14 mm² + 4 x 0,5 mm² DESINA CE



Marking for SL 803 C 08030012:

SAB BRÖCKSKES · D-VIERSEN · SL 803 C 4 x 2 x 0,14 mm² + 4 x 0,5 mm² DESINA CE

Construction:

Conductor:	bare copper strands with reference to VDE 0812
Insulation:	TPE
Colour code:	coloured
Stranding	
SL 802 C:	in layers
SL 803 C:	in layers or pairwise
	<i>acc. to dimension:</i>
Screen:	pairs with tinned copper wires braided or wrapped
Inner sheath:	TPE
Stranding:	cores/pairs twisted together in layers
Wrapping:	non-woven tape or netting tape
Screen:	tinned copper braiding
Wrapping:	non-woven tape
Sheath material:	PUR, TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2 with mat surface
Sheath colour:	SL 802 C: orange (RAL 2003) SL 803 C: green (RAL 6018)

Technical data:

Peak operating voltage	
SL 802 C:	max. 500 V
SL 803 C:	max. 350 V
Testing voltage:	core/core 2000 V core/screen 1200 V
Min. bending radius	
<i>fixed laying:</i>	5 x d
<i>flexible application:</i>	10 x d
<i>continuously flexible:</i>	12 x d
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range	
<i>fixed laying:</i>	-50/+90 °C
<i>flexible application:</i>	-40/+90 °C
Oil resistance:	very good - TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Weather resistance:	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“

C
13

Outstanding features:



- very good EMC characteristics
- very high flexibility
- very long service life
- adhesion-free installation
- oil resistant
- halogen-free
- PWIS uncritical
(PWIS = paint-wetting impairment substances)
- flexible at low temperatures
- DESINA® colours (see page C/4)



suitable for
resolvers and shaft encoders

item no.	dimension	sheath colour	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
motor feedback cable						
08020050	9 x 0,50	orange	0,16	7,8	66,2	97
transmission cable						
08030009	4 x 2 x 0,25 + 2 x 0,50	orange	0,11/0,16	7,8	51,8	81
08030010	4 x 2 x 0,25 + 2 x 1,00	orange	0,11/0,16	7,9	63,3	93
08030160	3 x 2 x 0,25 + 3 x 0,25 + 2 x 1,00	orange	0,11/0,16	7,9	65,8	96
08030040	3 x 2 x 0,25	orange	0,11	6,3	33,2	52
08030060	4 x 2 x 0,14 + (4 x 0,14) D + 4 x 1,00	orange	0,11/0,16	9,7	88,5	135
08030012	4 x 2 x 0,14 + 4 x 0,50	green	0,11/0,16	7,9	54,9	86
08030112	10 x 0,14 + 2 x 0,50	green	0,11/0,16	7,0	44,0	66
08030114	10 x 0,14 + 4 x 0,50	green	0,11/0,16	7,8	55,6	83
08030013	4 x 2 x 0,38 + 4 x 0,50	green	0,11/0,16	8,9	75,9	112
08030020	3 x (2 x 0,14 C) + 2 x 1,00	green	0,11/0,16	8,6	80,6	102
08030022	3 x (2 x 0,14 C) + 2 x (0,50 C)	green	0,11/0,16	8,8	87,6	108
08031050	3 x (2 x 0,14 D) + 4 x 0,14 + 4 x 0,22 + 2 x 0,50	green	0,11	9,5	77,9	121

Other dimensions and colours are possible on request.

Note: SIEMENS® is a registered trademark. It is only used for comparative purposes.
INDRAMAT® is a registered trademark of Bosch Rexroth AG. It is only used for comparative purposes.
DESINA® is a registered trademark of the German Machine Tool Builders' Association.

DESINA®
SIEMENS®
INDRAMAT®



www.sab-cable.com