

Besilen® - Silicone Cables

BiHFP-J

Besilen® insulated strands with Besilen® outer sheath and steel wire armouring for mechanical protection



Construction:	
Conductor:	tinned copper strands acc. to IEC 60228, VDE 0295, class 5
Insulation:	Besilen® EI2 acc. to EN 50363-1 + VDE 0207-363-1
Colour code:	coloured acc. to HD 308 (VDE 0293-308), from 6 cores black cores with consecutive numbers acc. to EN 50334 + VDE 0293-334, from 3 cores a green-yellow earth wire
Stranding:	in layers
Sheath material:	Besilen® EM9 acc. to EN 50363-2-1 + VDE 0207-363-2-1
Sheath colour:	reddish brown (similar RAL 3016)
Armour:	galvanized steel wire braiding

Technical data:	
Nominal voltage:	U ₀ /U 300/500 V
Testing voltage:	core/core 2000 V
Min. bending radius	
<i>fixed laying:</i>	5 x d
<i>flexible application:</i>	10 x d
Radiation resistance:	2 x 10 ⁷ cJ/kg
Temperature range	
<i>fixed laying:</i>	-40/+180 °C
<i>flexible application:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
Corrosiveness of conflagration gases:	IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases
Chem. resistance:	see chapter N „Technical Data“
Weather resistance:	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union see chapter N „Technical Data“

Outstanding features:	
	● halogen-free
	● flexible at low temperatures
	● heat resistant
	● protection against mechanical damage

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01430207	2 x 0,75	0,21	6,4	14,4	69
01430307	3 x 0,75	0,21	6,7	21,6	79
01430407	4 x 0,75	0,21	7,2	28,8	90
01430507	5 x 0,75	0,21	7,9	36,0	108
01430607	6 x 0,75	0,21	8,7	43,2	132
01430707	7 x 0,75	0,21	8,7	50,4	136
01430210	2 x 1,00	0,21	6,6	19,2	76
01430310	3 x 1,00	0,21	6,9	28,8	87
01430410	4 x 1,00	0,21	7,5	38,4	102
01430510	5 x 1,00	0,21	8,1	48,0	120
01430610	6 x 1,00	0,21	9,0	57,6	148
01430710	7 x 1,00	0,21	9,0	67,2	154
01430215	2 x 1,50	0,26	7,5	28,8	95
01430315	3 x 1,50	0,26	7,9	43,2	111
01430415	4 x 1,50	0,26	8,7	57,6	139
01430515	5 x 1,50	0,26	9,6	72,0	168
01430615	6 x 1,50	0,26	10,4	86,4	198

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
01430715	7 x 1,50	0,26	10,4	100,8	207
01430225	2 x 2,50	0,26	9,0	48,0	140
01430325	3 x 2,50	0,26	9,5	72,0	166
01430425	4 x 2,50	0,26	10,3	96,0	197
01430525	5 x 2,50	0,26	11,6	120,0	253
01430625	6 x 2,50	0,26	12,8	144,0	314
01430725	7 x 2,50	0,26	12,8	168,0	330
01430240	2 x 4,00	0,31	10,6	76,8	197
01430340	3 x 4,00	0,31	11,2	115,2	236
01430440	4 x 4,00	0,31	12,1	153,6	288
01430540	5 x 4,00	0,31	13,7	192,0	373
01430640	6 x 4,00	0,31	14,8	230,4	433
01430740	7 x 4,00	0,31	14,8	268,8	458
01430260	2 x 6,00	0,31	11,8	115,2	256
01430360	3 x 6,00	0,31	12,6	172,8	333
01430460	4 x 6,00	0,31	13,7	230,4	401
01430560	5 x 6,00	0,31	15,4	288,0	495

Other dimensions and colours are possible on request.