

# Besilen® - Silicone Cables

## BiHFGLP-J

Besilen® insulated strands with Besilen® outer sheath, fibre-glass tape and steel wire armouring for mechanical protection



### Construction:

<b>Conductor:</b>	tinned copper strands acc. to IEC 60228, VDE 0295, class 5
<b>Insulation:</b>	Besilen® EI2 acc. to EN 50363-1 + VDE 0207-363-1
<b>Colour code:</b>	coloured acc. to HD 308 (VDE 0293-308), from 6 cores black cores with consecutive numbers acc. to EN 50334 + VDE 0293-334, from 3 cores a green-yellow earth wire
<b>Stranding:</b>	in layers
<b>Sheath material:</b>	Besilen® EM9 acc. to EN 50363-2-1 + VDE 0207-363-2-1
<b>Sheath colour:</b>	reddish brown (similar RAL 3016)
<b>Wrapping:</b>	fibre-glass tape
<b>Armour:</b>	galvanized steel wire braiding

### Technical data:

<b>Nominal voltage:</b>	Uo/U 300/500 V
<b>Testing voltage:</b>	core/core 2000 V
<b>Min. bending radius</b>	
<i>fixed laying:</i>	5 x d
<i>flexible application:</i>	10 x d
<b>Radiation resistance:</b>	2 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
<i>fixed laying:</i>	-40/+180 °C
<i>flexible application:</i>	-25/+180 °C
<i>short-time use:</i>	+250 °C
<b>Halogen-free:</b>	acc. to IEC 60754-1 + VDE 0482-754-1
<b>Fire performance:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2
<b>Corrosiveness of conflagration gases:</b>	IEC 60754-2 + VDE 0482-754-2 - no development of corrosive conflagration gases
<b>Chem. resistance:</b>	see chapter N „Technical data“
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union, see chapter N „Technical data“

### Outstanding features:

- » halogen-free
- » flexible at low temperatures
- » heat resistant
- » protection against mechanical damage

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
01460207	2 x 0,75	0,21	6,8	14,4	73
01460307	3 x 0,75	0,21	7,1	21,6	82
01460407	4 x 0,75	0,21	7,6	28,8	96
01460507	5 x 0,75	0,21	8,3	36,0	112
01460607	6 x 0,75	0,21	9,1	43,2	138
01460707	7 x 0,75	0,21	9,1	50,4	142
01460210	2 x 1,00	0,21	7,0	19,2	79
01460310	3 x 1,00	0,21	7,3	28,8	90
01460410	4 x 1,00	0,21	7,9	38,4	107
01460510	5 x 1,00	0,21	8,5	48,0	131
01460610	6 x 1,00	0,21	9,4	57,6	154
01460710	7 x 1,00	0,21	9,4	67,2	160
01460215	2 x 1,50	0,26	7,9	28,8	99
01460315	3 x 1,50	0,26	8,3	43,2	116
01460415	4 x 1,50	0,26	9,1	57,6	145
01460515	5 x 1,50	0,26	10,0	72,0	175
01460615	6 x 1,50	0,26	10,8	86,4	205

item no.	no. of cores x cross section n x mm <sup>2</sup>	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
01460715	7 x 1,50	0,26	10,8	100,8	214
01460225	2 x 2,50	0,26	9,4	48,0	146
01460325	3 x 2,50	0,26	9,9	72,0	172
01460425	4 x 2,50	0,26	10,7	96,0	208
01460525	5 x 2,50	0,26	12,0	120,0	260
01460625	6 x 2,50	0,26	13,2	144,0	323
01460725	7 x 2,50	0,26	13,2	168,0	339
01460240	2 x 4,00	0,31	11,0	76,8	204
01460340	3 x 4,00	0,31	11,6	115,2	248
01460440	4 x 4,00	0,31	12,7	153,6	316
01460540	5 x 4,00	0,31	14,1	192,0	383
01460640	6 x 4,00	0,31	15,2	230,4	443
01460740	7 x 4,00	0,31	15,2	268,8	469
01460260	2 x 6,00	0,31	12,2	115,2	265
01460360	3 x 6,00	0,31	13,0	172,8	342
01460460	4 x 6,00	0,31	14,1	230,4	411
01460560	5 x 6,00	0,31	15,4	288,0	493

Other dimensions and colours are possible on request.